



# Calculation of Application Torques for Zürrer Gear Units

Dok.-Nr.: FOR-00..		Seite 1/4
	Datum	Visum
Erstellt:	04.03.2005	RDE
Freigabe:	14.03.2008	RDE

## Table torques

The static torques given in the tables are based on uniform, smooth servo-operation and on wear or maximum flank load. In other words, these values are merely theoretic.

Considered calculating factors are:

load factor	=	1.00
operating time factor	=	1.00
safety coefficient	=	1.00
life cycle	=	20'000 h
oil-sump temperature	=	80 ° C

Since, in practice, the applications are very diverse, it is essential to consider the given conditions by using the appropriate factors.

Under full load continuous running it is necessary to consider temperature limits! (The maximum oil – sump temperature of 80° C should not be exceeded).

### Load factor $B_k$

drive	type of load from the machines to be driven		
	uniform	medium shocks	heavy shocks
uniform	1.00	1.25	1.75
light shocks	1.25	1.50	2.00
medium shocks	1.50	1.75	2.25

### Operating time factor $B_D$

operating time	2-8 h.	8-12 h.	>12 h.
operating time factor	1.00	1.20	1.35

### Safety coefficient $S$

The safety coefficient should be allowed for according to experience ( $S = 1.2 - 1.5$ ).

### Efficiency

The gearing efficiency is given in the tables. For calculating the power it is indispensable to consider the power loss due to the following factors:

shaft sealings	2.5% each
ball bearings	3.5% each



## Calculation of Application Torques for Zürrer Gear Units

Dok.-Nr.: FOR-00..

Seite 2/4

Datum

Visum

Erstellt:

04.03.2005

RDE

Freigabe:

14.03.2008

RDE

churn loss = 5%  
coupling = 4%

**The overall efficiency is calculated as follows:**

$$\eta_g = \eta_z \times \eta_d \times \eta_w \times \eta_p \times \eta_k$$

**Formulas for determining power and torque data:**

$$a = \frac{v}{t_b} \quad (\text{m/s}^2)$$

$$F_u = m \times g + m \times a \quad (\text{for lifting axle}) \quad (\text{N})$$

$$F_u = m \times g \times \mu + m \times a \quad (\text{for driving axle}) \quad (\text{N})$$

$$T_{2\text{erf.}} = \frac{F_u \times d}{2000} \quad (\text{Nm})$$

$$n_2 = \frac{v}{d \times \pi} \times 60000 \quad (\text{min}^{-1})$$

$$i_{\text{Getr.}} = \frac{n_1}{n_2}$$

$$T_{2\text{zul.}} = \frac{T_{2\text{Tabelle}}}{B_k \times B_D \times S} \quad (\text{Nm})$$

**Condition  $T_{2\text{zul.}} > T_{2\text{erf.}}$  must be fulfilled!**

$$P_{\text{verf.}} = \frac{T_{2\text{erf.}} \times n_2}{9550 \times \eta_g} \quad (\text{kW})$$

### Calculating example:

values given:

lifting operation

mass to be moved  $m$  = 150 kg

speed  $v$  = 1.95 m/s

acceleration time  $t_b$  = 0.3 s

acceleration due to gravity  $g$  = 9.81 m/s<sup>2</sup>

pitch-circle dia. of pinion  $d$  = 108.00 mm (pinion on output shaft)

load factor  $B_k$  = 1.25

operating time factor  $B_D$  = 1.2

safety coefficient  $S$  = 1.2



## Calculation of Application Torques for Zürrer Gear Units

Dok.-Nr.: FOR-00..

Seite 3/4

Datum

Visum

Erstellt:

04.03.2005

RDE

Freigabe:

14.03.2008

RDE

motor rpm  $n_1 = 3000 \text{ min}^{-1}$

### Calculation process

$$a = \frac{v}{t_b} = \frac{1.95}{0.3} = 6.5 \text{ m / s}^2$$

$$F_u = m \times g + m \times a = 175 \times 9.81 + 175 \times 6.5 = 2854.25 \text{ N}$$

$$T_{2\text{erf.}} = \frac{F_u \times d}{2000} = \frac{2854.25 \times 108}{2000} = 154.12 \approx 155 \text{ Nm}$$

$$n_2 = \frac{v}{d \times \pi} \times 60000 = \frac{1.95}{108 \times \pi} \times 60000 = 344.835 \approx 345 \text{ min}^{-1}$$

$$i_{\text{Getr.}} = \frac{n_1}{n_2} = \frac{3000}{345} = 8.6956$$

assumed SGH74/1 with  $T_{2\text{Tabelle}} = 290$  at  $i = 8.75:1$  and  $n_1 = 3000$

$$T_{2\text{zul.}} = \frac{T_{2\text{Tabelle}}}{B_K \times B_D \times S} = \frac{290}{1.25 \times 1.2 \times 1.2} = 161 \text{ Nm}$$

### Condition

$$T_{2\text{zul.}} > T_{2\text{erf.}} = 161 \text{ Nm} > 155 \text{ Nm} = \text{fulfilled}$$

### Overall efficiency of gear SGH74/1 (single-sided output shaft):

$$\eta_g = \eta_z \times \eta_d \times \eta_w \times \eta \times \eta_k = 0.94 \times 0.95 \times 0.86 \times 0.95 \times 0.96 = 0.70$$

### Calculation of power requirement

$$P_{\text{erf.}} = \frac{T_{2\text{erf.}} \times n_2}{9550 \times \eta_g} = \frac{155 \times 345}{9550 \times 0.70} = 8 \text{ kW}$$

It is, however, more useful to calculate the table value by means of the required torque and the according factors:

$$T_{2\text{Tabelle}} = T_{2\text{erf.}} \times B_K \times B_D \times S = 155 \times 1.25 \times 1.2 \times 1.2 = 279 \text{ Nm}$$

This value allows now to select the appropriate gear in our catalogue (Take the next higher value).



# Calculation of Application Torques for Zürrer Gear Units

Dok.-Nr.: FOR-00..	Seite 4/4	
	Datum	Visum
Erstellt:	04.03.2005	RDE
Freigabe:	14.03.2008	RDE

## Symbols

$a$	=	acceleration or retardation	(m/s <sup>2</sup> )
$B_D$	=	operating time factor	
$B_k$	=	load factor	
$d$	=	pitch-circle dia. of pinion	(mm)
$g$	=	acceleration due to gravity	(9.81m/s <sup>2</sup> )
$m$	=	mass	(kg)
$n_1$	=	gearbox input rpm	(min <sup>-1</sup> )
$n_2$	=	gearbox output rpm	(min <sup>-1</sup> )
$t_b$	=	acceleration time	(s)
$i$	=	gear ratio	
$v$	=	travelling / lifting speed	(m/s)
$F_u$	=	peripheral force at the pinion	(N)
$P_{1\text{ erf.}}$	=	necessary gearbox input power	(kW)
$S$	=	safety coefficient	
$T_{2\text{ zul.}}$	=	admissible torque	(Nm)
$T_{2\text{ erf.}}$	=	necessary torque	(Nm)
$T_{2\text{ Tabelle}}$	=	torque according table values	(Nm)
$\eta_g$	=	overall efficiency	
$\eta_z$	=	gearing efficiency	
$\eta_d$	=	efficiency shaft seal	
$\eta_w$	=	efficiency ball bearings	
$\eta_p$	=	efficiency churning	
$\eta_k$	=	efficiency coupling	
$\mu$	=	coefficient of friction	
$\pi$	=	3.14159	

10.04.2001 R. Debrunner