Material Safety Data Sheet

according 93/112/EEC

Henri Hotz AG, 8600 Dübendorf, Material Safety Data Sheet Olyt ZO - 31/61, 77-46 Edition 00, April 1998

Page 1 of 4

1. <u>Substance / Preparation and Company Identification</u>

Special oil Olyt ZO - 31/61

Company: Henri Hotz AG Sunnhaldenstrasse 6 8600 Dübendorf Tel.: 01 821 63 66

Emergency Contact: Tel.: 01 821 63 66 FAX: 01 820 10 67

Art.-No.: 77-46

2. <u>Composition / Information on Ingredients</u>

<u>Chemical Characterization</u>

Blend of highliy refined mineral oils and additives.

Dangerous Ingredients
None

3. <u>Hazards Identification</u>

Special instruction for human and environment: Prolonged exposure may give rise to dermatitis. Hazardous for soil, drain and surface water.

4. First Aid Measures

General:

Remove solled clothes.

Inhalation:

Immediate fresh air, call in an emergency doctor.

Skin Contact:

Wash the skin with soap and water. In case of dermatitis seek medical attention.

Eye Contact:

Rinse the eyes immediately with water for at least 15 minutes. In case of eye irritation, seek medical attention.

Ingestion:

Do not induce vomiting. Call in the emergency doctor.

Henri Hotz AG, 8600 Dübendorf, Material Safety Data Sheet Olyt ZO - 31/61, 77-46 Edition 00, April 1998

Page 2 of 4

5. Fire Fighting Measures

Suitable Extinguishing media: Carbon dioxide, dry powder, foam

Unsuitable is: Water let

6. Accidental Release Measures

Personal Precautions:

Avoid contact with eyes and skin.

Environmental Precautions:

Prevent contamination of soil, drains and surface water. Otherwise notify the police or the fire service at once.

Methods for Cleaning:

Take up and place in sulfable container for disposal according to the rules.

7. Handling and Storage

Handling:

Avoid longer skin contact. Do not eat, drink or smoke at the workplace.

Fire and explosion protection:

Formation of hazardous mixtures in the air under high temperatures or when sprayed is possible.

Hazard code (BVD): F 4 I Fu PN2 (Swiss legislation)

Storage:

Store vessels out of reach of unauthorized persons and protect againts heat and naked flame. Recommended storage temperatures: 0°C to 50°C.

8. Exposure Controls / Personal Protection

Technical Protective Measures:

Prevent the formation of oil vapour and mist.

Exposure Control Limits:

MAC value for mineral oil mist (SUVA-list):

5 mg/m³

Personal Protection Measures:

Hand protection:

Wear suitable gloves.

Eye protection:

Wear suitable goggles when there is a risk of spraying.

Respiratory protection:

None

Skin protection:

Wear overalls and closed footwear.

Working hyglene:

Avoid sustained, frequent and intensive contact with the skin; if necessary wear protective gloves and an apron. Before starting work apply a suitable protective agent to the skin. After work as well as before pauses for meals wash grease-contaminated hands thoroughly and apply a sultable cleaning agent. After cleaning, replace grease thereby lost by a greasy skin cream. Clothing saturated with oil should be immediately cleaned. Do not carry oily rags and the like in the trouser pockets. Avoid breathing oil vapour or mist. Keep well away from foodstuffs, beverages and fodder.

9. Physical and Chemical Properties

Appearance at 20 °C

liquid

Colour

yellow-brown

Odour

specific as product

Density at 15°C Kin. viscosity at 40°C

895 kg/m2

ISO 3675

220 mm²/s

ISO 3104

Kin. Viscosity at 100°C Pourpoint

19,9 mm²/s -18°C

ISO 3104

Water solubility

Insoluble

ISO 3018

Flashpoint

280°C

ISO 2592

10. Stability and Reactivity

Hazardous reactions:

When correctly stored and handled: None

Thermal decomposition:

At normal pressure cannot be destilled without decomposing.

Dangerous decomposition products:

Monoxide of carbon.

11. Toxicological Information

Oral Toxicity:

LD 50 / oral / rats: > 2000 mg/kg

Toxicity class / BAG-T No. (CH-legislation)

free / 61 72 00

Henri Hotz AG, 8600 Dübendorf, Material Safety Data Sheet Olyt ZO - 31/61, 77-46 Edition 00, April 1998

Page 4 of 4

12. <u>Ecological Information</u>

Water hazard class (EC): 2

Can be extracted by an oil separator.

On no account allow the product to enter the drains, watercourses or soil. Comply with the rules for handling special refuse.

13. <u>Disposal Considerations</u>

Disposal should be in compliance with federal state and local laws.

Switzerland:

VVS category code number: 1481

14. Transport Information

UN

ADR/SDR

IATA

free

free

free

Not a hazardous material as defined in transport regulations.

15. Regulatory Information

Not classified as dangerous under Directive 88/379/EEC and Directive 96/54/EEC (22. Adaption of Directive 67/548/EEC of 30.9.96)

16. Other Informations

The information contained in this material safety data sheet is based on the present state of our knowledge and experience and serves the purpose of describing the product in relation to any safety requirements that may be in force. It does not represent an assurance of the product described.